
## Polyset

Expansion Joint Systems for PERFORMANCE

## Ply-Seal<sup>®</sup> Joint Detail with Ply-Seal<sup>®</sup> FG (Forming Seal)



The **Ply-Seal**<sup>®</sup> **Joint System** with **Ply-Seal**<sup>®</sup> **FG** offers a convenient, durable, waterproof expansion joint system. The **Ply-Seal**<sup>®</sup> **FG** is a full depth, waterproof seal forming the joint gap as the contractor pours the concrete. The top section of the **Ply-Seal**<sup>®</sup> **FG** is removed after concrete cure at a prefab tear strip section, creating a cavity for the primary seal: **Ply-Seal**<sup>®</sup>.

The seals may be field-welded for a monolithic waterproof joint. The **joint system** has a movement range equal to the joint width. These systems are user-friendly, quickly installed, and allow the structure to be returned to use shortly after installation. The system is an ideal expansion joint seal for flood control channels, approach slabs, bridge decks, sea walls, airport tarmacs, and other commercial structures where waterproof joint seals with full-depth protection are required. The **joint systems** may be installed against steel, concrete, wood, and other construction materials in vertical or horizontal applications. **Ply-Seal**<sup>®</sup> **FG Joint Systems** are resistant to abrasion, oxidation, oils, water, cleaning solutions, salt and other materials that may come in contact with the product.

## Joint Design Chart (for Primary Seal)

Model Number	Jt. Gap (in.) @ 60°F	Rec.* Seal Size (w x d)	Movement Range (in.)
#1.38	1	1 3/8 x 2	0.5 - 1.8
#1.63	1 1/4	1 5/8 x 2	0.6 - 2.1
#2.00	1 1/2	2 x 2	0.8 - 2.6
#2.38	1 3/4	2 3/8 x 2	0.9 - 3.1
#2.75	2	2 3/4 x 2	1.1 - 3.6
#3.00	2 1/4	3 x 2 1/2	1.2 - 3.9
#3.25	2 1/2	3 1/4 x 2 1/2	1.3 - 4.2
#3.50	2 3/4	3 1/2 x 2 1/2	1.4 - 4.5
#4.00	3	4 x 3	1.6 - 5.2
#4.50	3 1/2	4 1/2 x 3	1.8 - 5.8
#5.00	4	5 x 3 1/2	2.0 - 6.5

\*This chart is based on 60% compression and 30% tension. Please contact us for project-specific recommended sizes. Many other sizes are available.

Limited Warranty: Polyset Company Inc. makes no warranty, expressed or implied, including any warranty of merchantability of fitness for a particular purpose. The sole remedy of Purchaser for any claim concerning this product, including, but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the replacement of product or refund of the purchase price, at the discretion of Polyset Company Inc. Any claims concerning this product shall be submitted in writing within one year of the delivery date of this product to Purchaser and any claims not presented within that period are waived by Purchaser. IN NO EVENT SHALL POLYSET COMPANY INC. BE LIABLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDES LOSS OF PROFITS) OR PUNITIVE DAMAGES. Copyright © 2016 Polyset Company, Inc. All rights reserved. Revised 9/16.